



- 16 - HOLES $\phi 14$ THRO' EQUI-SPACED ON 851 P.C.D.
- 12 - HOLES $\phi 16.7$ THRO' EQUI-SPACED ON 641.3 P.C.D.
- 10 PLATE COUPLING - TOTAL THICKNESS 12mm. HUB SECURING BOLTS TO BE TIGHTENED TO A TORQUE OF 1350Nm
- 4 - HOLES M16 THRO'
- 4 - HOLES $\phi 42$ THRO'

CORE	C of G	WEIGHT
R	851	5336kg
S	866	5584kg
T	884	5934kg

MOD	ISSUE	DRAWN	DATE	ALTERATION
4/6344/49	B	RT	18/05/04	851 DIA WAS 679.5, 641.3 WAS 543 DIA
4/6344/40	A	RT	16/12/03	ORIGINAL ISSUE

CERTIFIED PRINT		
ONLY IF SIGNED		
BY		
DATE		
DRAWN	RT	16/12/03
CHECKED	RT	1/06/04
APPROVED	RT	4-6-04

P80 R/S/T ALTERNATOR
 SAE00/21 - 500 CHT
 IP23 COVER AT DE

**CONFIDENTIAL PROPERTY OF
 NEWAGE INTERNATIONAL LTD**

SCALE	FIRST W.O. 0852305
1:10	UNIT OF MEASUREMENT MILLIMETRES (mm)
C80-2193	ISSUE B
SHEET 1 OF 1 SHEETS	

