



16 - HOLES ø 14  
THRO' EQUI-SPACED  
ON 679,5 P.C.D.

12 - HOLES ø 16,7  
THRO' EQUI-SPACED  
ON 543 P.C.D.

10 PLATE COUPLING - TOTAL THICKNESS  
12mm. HUB SECURING BOLTS TO BE  
TIGHTENED TO A TORQUE OF 1350Nm

4 - HOLES M16 THRO'  
4 - HOLES ø 42 THRO'

CORE	C of G	WEIGHT
R	851	5336kg
S	866	5584kg
T	884	5934kg



CERTIFIED PRINT		
ONLY IF SIGNED		
BY		
DATE		
DRAWN	RT	16/12/03
CHECKED	RT	20/01/04
APPROVED	NO	21.01.04

P80 R/S/T ALTERNATOR  
SAE0/18 - 500 CHT  
IP23 COVER AT DE

SCALE FIRST W.O. 0852305

1:10 UNIT OF MEASUREMENT  
MILLIMETRES (mm)

CONFIDENTIAL PROPERTY OF  
NEWAGE INTERNATIONAL LTD

C80-2194

ISSUE  
A

SHEET 1 OF 1 SHEETS

4/6344/40	A	RT	16/12/03	ORIGINAL ISSUE
MOD	ISSUE	DRAWN	DATE	ALTERATION