

Cummins Data Classification: Cummins Confidential

This document (and the information shown thereon) is **Confidential and Proprietary** and shall not be disclosed to others in hard copy or electronic form, reproduced by any means, or used for any purpose without written consent of Cummins Inc. Part Number: A058H236 Part Revision: B Part Name: ARRANGEMENT,GENERATOR ROTOR TORSIONAL Drawing Category: Outline State: Released Sheet 1 of 2

L FNESS:- THE STIFFNESS OF THE SHAFT BETWEEN THE CORE GLAND THE SHAFT EXTENSION Q. 10 ⁶ KGG/MARDIAN 3 EFFECT OF MAIN ROTOR CORE IS NOT INCLUDED IN 10 ⁶ KGG/MARDIAN 3 EFFECT OF MAIN ROTOR STRESS LEVEL IN THE SHAFT IS N/M FOR SPECT ANAL 00 0.95 TO I.X ADMINAL 88.94 X 10 N/M FOR RUN THROUGH CONDITIONS, FOR MACHINES, FOR MARINE AUTORNITIES, THEIR APPROPRIATE 88.94 X 10 N/M FOR MARINE AUTORNITIES, THEIR APPROPRIATE 88.94 X 10 N/M FOR MARINE AUTORNITIES, THEIR APPROPRIATE APPLY WERATOR TECHNOLOGIES LTD BALANCE POTORS TO H INTERNATIONAL STD BS ISO 1940 PARTS I AND 2. ADE 2.5 NEED MAGNETIC PULL (U.M.P.) FORCES TACT CUMMINS GENERATOR TECHNOLOGIES LTD BALANCE POTORS TO H INTERNATIONAL STD BS ISO 1940 PARTS I AND 2. ADE 2.5 NEED MAGNETIC PULL (U.M.P.) FORCES TACT CUMMINS GENERATOR TECHNOLOGIES LTD				
CORE CAND THE SHAFT EXTENSION C. IO® KGGW/RADIAN SEFFECT OF MAIN ROTOR CORE IS NOT INCLUDED IN K SEFFECT OF MAIN ROTOR CORE IS NOT INCLUDED IN K STARLI: STEEL - C40E TO BSEN 10083-2 2006 STMARINE AUTHORITIES WHEN APPROPRIATE) J COMMENDED VIBRATORY STRESS LEVEL IN THE SHAFT IS N/m ² FOR SPEED RANGE OF 0.95 TO 1.1 X NOMINAL J KERATOR TECHNOLOGIES LTD SHOULD BE NOTIFIED OF ANY J J WERATOR TECHNOLOGIES LTD SHOULD BE NOTIFIED OF ANY I COMPLYING WITH THESE RULES I AND 2. J NEERATOR TECHNOLOGIES LTD BALANCE ROTORS TO I H INTERNATIONAL STD BS ISO 1940 PARTS I AND 2. J MCED MAGNETIC PULL (U.M.P.) FORCES I TACT CUMMINS GENERATOR TECHNOLOGIES LTD I H G G G J I MACH NES, GENERATOR TECHNOLOGIES LTD I H INTERNATIONAL STO BS G I I G G G I I G G I I I G G G I I I I G <	4	3	2	
CORE CAND THE SHAFT EXTENSION C. IO® KGGW/RADIAN SEFFECT OF MAIN ROTOR CORE IS NOT INCLUDED IN K SEFFECT OF MAIN ROTOR CORE IS NOT INCLUDED IN K STARLI: STEEL - C40E TO BSEN 10083-2 2006 STMARINE AUTHORITIES WHEN APPROPRIATE) J COMMENDED VIBRATORY STRESS LEVEL IN THE SHAFT IS N/m ² FOR SPEED RANGE OF 0.95 TO 1.1 X NOMINAL J KERATOR TECHNOLOGIES LTD SHOULD BE NOTIFIED OF ANY J J WERATOR TECHNOLOGIES LTD SHOULD BE NOTIFIED OF ANY I COMPLYING WITH THESE RULES I AND 2. J NEERATOR TECHNOLOGIES LTD BALANCE ROTORS TO I H INTERNATIONAL STD BS ISO 1940 PARTS I AND 2. J MCED MAGNETIC PULL (U.M.P.) FORCES I TACT CUMMINS GENERATOR TECHNOLOGIES LTD I H G G G J I MACH NES, GENERATOR TECHNOLOGIES LTD I H INTERNATIONAL STO BS G I I G G G I I G G I I I G G G I I I I G <				
E) RIAL: STEEL - CAOE TO BEEN 10083-2 2006 SY MARINE AUTHORITIES WHEN APPROPRIATE COMMENDED VIBRATORY STRESS LEVEL IN THE SHAFT IS NUMBY FOR SPEED RANGE OF 0.95 TO 1.1 X NOMINAL BS 94 X 10 NUMBY FOR THIN THROUGH CONDITIONS, FOR MACHINES, FOR MARINE AUTHORITIES, THEIR APPROPRIATE APPLY NERATOR TECHNOLOGIES LID SHOULD BE NOTIFIED OF ANY COMPLYING WITH THESE RULES NERATOR TECHNOLOGIES LID BALANCE ROTORS TO H INTERNATIONALIONAL IS ISO 1940 PARTS I AND 2. ADE 2.5 NCED MAGNETIC PULL (U.M.P.) FORCES TACT CUMMINS GENERATOR TECHNOLOGIES LID	CORE CAN	ID THE SHAFT EXTEI	NSION ¢	
3Y MARINE AUTHORITIES WHEN APPROPRIATE) COMMENDED VIBRATORY STRESS LEVEL IN THE SHAFT IS N/M2 FOR SPEED RANGE OF 0.95 TO 1.1 X NOMINAL 68.94 X 10 N/M2 FOR RUN THROUGH CONDITIONS, FOR MACHINES, FOR MARINE AUTHORITIES, THEIR APPROPRIATE APPLY J WERATOR TECHNOLOGIES LTD SHOULD BE NOTIFIED OF ANY COMPLYING WITH THESE RULES INTERNATIONAL STD BS ISO 1940 PARTS I AND 2. ADE 2.5 TACT CUMMINS GENERATOR TECHNOLOGIES LTD I H INTERNATIONAL STD BS ISO 1940 PARTS I AND 2. ADE 2.5 TACT CUMMINS GENERATOR TECHNOLOGIES LTD I H I MCED MACKTIC PULL (U.M.P.) FORCES TACT CUMMINS GENERATOR TECHNOLOGIES LTD I	G EFFECT (E)	DF MAIN ROTOR COR	E IS NOT INCLUDED	K
N/m ² FOR SPEED RANGE OF 0.95 TO 1.1 X NOMINAL 63.94 X 10 N/m ² FOR NUM TROUGH COUDITIONS, FOR MACHINES. FOR MARINE AUTHORITIES, THEIR APPROPRIATE APPLY WERATOR TECHNOLOGIES LTD SHOULD BE NOTIFIED OF ANY COMPLYING WITH THESE RULES NERATOR TECHNOLOGIES LTD BALANCE ROTORS TO INTERATION TECHNOLOGIES LTD BALANCE ROTORS TO INTERATION TECHNOLOGIES LTD BALANCE ROTORS TO INTERATOR TECHNOLOGIES LTD BALANCE ROTORS TO INTERATOR TECHNOLOGIES LTD BALANCE ROTORS TO INTERATOR TECHNOLOGIES LTD BALANCE ROTORS REATOR TECHNOLOGIES LTD H H INTERMATIONAL STD BS ISO 1940 PARTS I AND 2. ADE 2.5 NED MAGNETIC PULL (U.M.P.) FORCES TACT CUMMINS GENERATOR TECHNOLOGIES LTD H G G INTO CONVERT TO INTERSTOR FOR TOOL IN FACTORS D Kg m ² 1 b ft ² N/m ² INTO CONVERT TO INTO CONVERT				
MACHINES. FOR MARINE AUTHORITIES, THEIR APPROPRIATE APPLY VERATOR TECHNOLOGIES LID SHOULD BE NOTIFIED OF ANY COMPLYING WITH THESE RULES UNAGENETIC TO TECHNOLOGIES IT AND 2. ADE 2.5 NCED MACNETIC PULL (U.M.P.) FORCES TACT CUMMINS GENERATOR TECHNOLOGIES LTD H G F E CONVERSION FACTORS NCED MACNETIC PULL (U.M.P.) FORCES TACT CUMMINS GENERATOR TECHNOLOGIES LTD H G CONVERSION FACTORS NCED MACNETIC PULL (U.M.P.) FORCES TACT CUMMINS GENERATOR TECHNOLOGIES LTD CONVERSION FACTORS CONVERT TO DIVIDE BY kg m ² 1b ft ² 0.04214 kg cm/rod 1b in/rod 1.1521246 N/m ² 1b ff in ² 6894.76 C B Cummins Generator Technologies L1 AK HL: WILLIMITERS SIZE: AI SCHEETICS CLOB STRIM ASME TI 5.2009 THIB AMBLE HOMOCION	COMMENDED N/m ² FOR 68.94 X IC	VIBRATORY STRESS SPEED RANGE OF O N/m ² FOR RIIN TH	LEVEL IN THE SH .95 TO I.I X NOM ROUGH CONDITIONS	AFT IS INAL FOR
COMPLYING WITH THESE RULES NERATOR TECHNOLOGIES LTD BALANCE ROTORS TO H INTERNATIONAL STD BS ISO 1940 PARTS I AND 2. ADE 2.5 NEED MAGNETIC PULL (U.M.P.) FORCES TACT CUMMINS GENERATOR TECHNOLOGIES LTD H H G F E CONVERSION FACTORS TO CONVERT TO DIVIDE BY kg m ² 1b ft ² 0.04214 kg cm/r ad 1bin/r ad 1.1521246 N/m ² 1b ft/in ² 6894.76 C B Cummins Generator Technologies L1 AM HLLINTERS SIZE: A1 SCALET2.2 PICE Create Parametric A C A C C C C C C C C C C C C C	MACHINES. APPLY	FOR MARINE AUTH	ORITIES, THEIR AN	
H INTERNATIONAL STD BS ISO 1940 PARTS I AND 2. ADE 2.5 NCED MAGNETIC PULL (U.M.P.) FORCES TACT CUMMINS GENERATOR TECHNOLOGIES LTD H H G F E <u>CONVERSION FACTORS</u> <u>TO CONVERT TO DIVIDE BY</u> <u>kg m² Ib ft² 0.04214</u> <u>kg m² Ib ft² 0.6894.76</u> C B <u>Cummins Generator Technologies</u> <u>(1 AME IN: MILLINTERS</u> SIZE: AI SCALE:12.0 <u>CONSTEM</u> <u>ASME Y14.5-2009</u> <u>THE MALE FROACTION</u> <u>PTC[®] Cred[®] Parametric A</u>				OF ANY
I TACT CUMMINS GENERATOR TECHNOLOGIES LTD H H G F E <u>CONVERSION FACTORS</u> <u>TO CONVERSION FACTORS</u> <u>TO CONVERT TO DIVIDE BY</u> <u>kg m² Ib ft² 0.04214</u> <u>kg m² Ib ft² 0.04214</u> <u>kg m² Ib ft² 0.04214</u> <u>kg m² Ib ft² 0.04214}</u> <u>kg m² Ib ft² 0.04214} <u>kg m² Ib ft² 0.04214}</u> <u>kg m² Ib ft² 0.04214} <u>kg m² 0.04216} <u>Kg m² 0.042</u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u></u>				ND 2.
Image: Science and Transmissions and The Initial Matters State Transmiss Cenerator Technologies To Aske Transmissions and The Initial Matters State Transmiss Cenerator Technologies To Aske Transmissions and The Initial Matters State Transmiss Cenerator Technologies To Aske Transmissions and The Initial Matters State Transmissions and The Ininitial Matters State	NCED MAGNE			
CONVERSION FACTORS F E D <u>TO CONVERT TO DIVIDE BY</u> <u>kg m² 1b 0.453592</u> <u>kg m² 1b ft² 0.04214</u> <u>kg cm/rad 1b in/rad 1.1521246</u> <u>N/m² 1b f/ i n² 6894.76</u> C B Cummins Generator Technologies (1) ARE IN: " DIMENSIONS ARE IN: MILLIMETERS 1) ARE IN: " DIMENSION RO AND TOLERANCING PER: ASME Y14.5-2009	it comm	2		
CONVERSION FACTORS F E D <u>TO CONVERT TO DIVIDE BY</u> <u>kg m² 1b 0.453592</u> <u>kg m² 1b ft² 0.04214</u> <u>kg cm/rad 1b in/rad 1.1521246</u> <u>N/m² 1b f/ i n² 6894.76</u> C B Cummins Generator Technologies (1) ARE IN: " DIMENSIONS ARE IN: MILLIMETERS 1) ARE IN: " DIMENSION RO AND TOLERANCING PER: ASME Y14.5-2009				
Image: State IN: MILLIMETERS SIZE: A1 SCALE:1:2.8 Some State IN: MILLIMETERS SIZE: A1 SCALE:1:2.8				Н
Image: State IN: MILLIMETERS SIZE: A1 SCALE:1:2.8 Some State IN: MILLIMETERS SIZE: A1 SCALE:1:2.8				
Image: State IN: MILLIMETERS SIZE: A1 SCALE:1:2.8 Some State IN: MILLIMETERS SIZE: A1 SCALE:1:2.8				C
E CONVERSION FACTORS TO CONVERT TO DIVIDE BY kg Ib 0.453592 kg m ² Ib ft ² 0.04214 kgcm/r ad Ib in/r ad I.1521246 N/m ² Ib f/ in ² 6894.76 C C B Cummins Generator Technologies DIMENSIONS ARE IN: MILLIMETERS 1 ARE IN: DIMENSIONS AND TOLERANCING PER: A SME Y14.5-2009 THIRD ANGLE PROJECTION PIC® Cree® Porometric A				G
E CONVERSION FACTORS TO CONVERT TO DIVIDE BY kg Ib 0.453592 kg m ² Ib ft ² 0.04214 kgcm/r ad Ib in/r ad I.1521246 N/m ² Ib f/ in ² 6894.76 C C B Cummins Generator Technologies DIMENSIONS ARE IN: MILLIMETERS 1 ARE IN: DIMENSIONS AND TOLERANCING PER: A SME Y14.5-2009 THIRD ANGLE PROJECTION PIC® Cree® Porometric A				
E CONVERSION FACTORS TO CONVERT TO DIVIDE BY kg Ib 0.453592 kg m ² Ib ft ² 0.04214 kgcm/r ad Ib in/r ad I.1521246 N/m ² Ib f/ in ² 6894.76 C C B Cummins Generator Technologies DIMENSIONS ARE IN: MILLIMETERS 1 ARE IN: DIMENSIONS AND TOLERANCING PER: A SME Y14.5-2009 THIRD ANGLE PROJECTION PIC® Cree® Porometric A				F
CONVERSION FACTORS TO CONVERT TO Ng 1b 0.453592 kg 1b 0.453592 kgm² 1b ft² 0.04214 kgcm/rad 1bin/rad 1.1521246 N/m² 1bf/in² 6894.76 Cummins Generator Technologies DIMENSIONS ARE IN: MILLIMETERS SIZE: A1 CAD SYSTEM ARE IN: - THRD ANGLE PROJECTION PTC® Cree® Parametric				'
CONVERSION FACTORS TO CONVERT TO Ng 1b 0.453592 kg 1b 0.453592 kgm² 1b ft² 0.04214 kgcm/rad 1bin/rad 1.1521246 N/m² 1bf/in² 6894.76 Cummins Generator Technologies DIMENSIONS ARE IN: MILLIMETERS SIZE: A1 CAD SYSTEM ARE IN: - THRD ANGLE PROJECTION PTC® Cree® Parametric				
CONVERSION FACTORS TO CONVERT TO Ng 1b 0.453592 kg 1b 0.453592 kgm² 1b ft² 0.04214 kgcm/rad 1bin/rad 1.1521246 N/m² 1bf/in² 6894.76 Cummins Generator Technologies DIMENSIONS ARE IN: MILLIMETERS SIZE: A1 CAD SYSTEM ARE IN: - THRD ANGLE PROJECTION PTC® Cree® Parametric				E
DIMENSIONIS AND TOLERANCING PER: ASME Y14.5-2009 THERD ANGLE PROJECTION THERD ANGLE PROJECTION THERD ANGLE PROJECTION THERD ANGLE PROJECTION TO CONVERT TO DIVIDE BY 0.453592 0.453592 0.04214				_
DIMENSIONIS AND TOLERANCING PER: ASME Y14.5-2009 THERD ANGLE PROJECTION THERD ANGLE PROJECTION THERD ANGLE PROJECTION THERD ANGLE PROJECTION TO CONVERT TO DIVIDE BY 0.453592 0.453592 0.04214		CONVERSI	ON FACTORS	-
kgcm/rad 1bin/rad 1.1521246 N/m ² 1bf/in ² 6894.76 C B Cummins Generator Technologies L ARE IN: - SIZE: A1 SCIMENSIONING AND TOLERANCING PER: SIZE: A1 ASME Y14.5-2009 THIRD ANGLE PROJECTION PTC® Cree® Porometric		TO CONVERT	TO DIVIDE B	
N/m² 1 b f / i n² 6894.76 C B Cummins Generator Technologies () ARE IN: - C DIMENSIONS ARE IN: MILLIMETERS () ARE IN: - SIZE: A1 SCALE:1:2.8 Common Source Composition of the second street	-		ft ² 0.04214	<u>-</u>
Cummins Generator Technologies DIMENSIONS ARE IN: MILLIMETERS SIZE: A1 SCALE:1:2.8 DIMENSIONING AND TOLERANCING PER: ASME Y14.5-2009 THIRD ANGLE PROJECTION PTC® Cree® Parametric A				
Cummins Generator Technologies DIMENSIONS ARE IN: MILLIMETERS SIZE: A1 SCALE:1:2.8 DIMENSIONING AND TOLERANCING PER: ASME Y14.5-2009 THIRD ANGLE PROJECTION PTC® Cree® Parametric A				С
Cummins Generator Technologies DIMENSIONS ARE IN: MILLIMETERS SIZE: A1 SCALE:1:2.8 DIMENSIONING AND TOLERANCING PER: ASME Y14.5-2009 THIRD ANGLE PROJECTION PTC® Cree® Parametric A				
Cummins Generator Technologies DIMENSIONS ARE IN: MILLIMETERS SIZE: A1 SCALE:1:2.8 DIMENSIONING AND TOLERANCING PER: ASME Y14.5-2009 THIRD ANGLE PROJECTION PTC® Cree® Parametric A				
DIMENSIONS ARE IN: MILLIMETERS SIZE: A1 SCALE:1:2:8 C J ARE IN: - OTMENSIONING AND TOLERANCING PER: ASME Y14.5-2009 THIRD ANGLE PROJECTION PTC® Cree® Parametric A				В
DIMENSIONS ARE IN: MILLIMETERS SIZE: A1 SCALE:1:2:8 C J ARE IN: - OTMENSIONING AND TOLERANCING PER: ASME Y14.5-2009 THIRD ANGLE PROJECTION PTC® Cree® Parametric A	Cummins	Generator Tec	hnologies	nmin ⁵
ASME Y14.5-2009 THIRD ANGLE PROJECTION PTC® Crea® Parametric A	DIMENSIONS ARE [] ARE	IN: MILLIMETERS SIZE:	A1 SCALE:1:2.8	•
4 3 2 1			$\Psi \cup$	
	4	3	2	1

Document Generated: 10JAN2023 10:13 GMT

	5			Part Number:	A058H236	
	nmins	Change Notice	CN00081951	Alternates		
CU		Manufacturer Part (N	IEP) No	Usage	Production Only	
	®	Release Phase Code	e Production (P)	Drawing	Number: DS47120409	
		External Regulations	No External Regulati	Specification	Revision: A	3D image provided when available for visual reference only.
awing Re	vision Information	1				
escription of ote: Change in	Change(s) nformation is provided for	reference only and does n	ot supersede the drawing's prim	ary content.		
INOR AMEN	IDMENTS					
DMINISTRA	TIVE CHANGE(S) TO	PART ATTRIBUTES, BI	LL OF MATERIAL, OR ASSO	OCIATED SPECIFICATION	NS.	
awing Au	thorization					
annig / a	~					
rafter	Aishwarya Rajaram	Shelar			Date 10JAN2023	
hecker	Aishwarya Rajaram Kuldeep Dilip Pawar				Date 10JAN2023	
hecker						
hecker	Kuldeep Dilip Pawar				Date 10JAN2023	
hecker	Kuldeep Dilip Pawar				Date 10JAN2023	
hecker	Kuldeep Dilip Pawar				Date 10JAN2023	
hecker	Kuldeep Dilip Pawar				Date 10JAN2023	
hecker	Kuldeep Dilip Pawar				Date 10JAN2023	
hecker	Kuldeep Dilip Pawar				Date 10JAN2023	
hecker	Kuldeep Dilip Pawar				Date 10JAN2023	
hecker	Kuldeep Dilip Pawar				Date 10JAN2023	
hecker	Kuldeep Dilip Pawar				Date 10JAN2023	
hecker	Kuldeep Dilip Pawar				Date 10JAN2023	
hecker	Kuldeep Dilip Pawar				Date 10JAN2023	
hecker	Kuldeep Dilip Pawar				Date 10JAN2023	
Checker	Kuldeep Dilip Pawar				Date 10JAN2023	
Drafter Checker Approver	Kuldeep Dilip Pawar				Date 10JAN2023	

Cur **Cummins Confidential**

in hard copy or electronic form, reproduced by any means, or used for any purpose without written consent of Cummins Inc.

Part Name: ARRANGEMENT, GENERATOR ROTOR TORSIONAL Drawing Category: Outline State: Released Sheet 2 of 2